
OLE ALMEBORG A/S

Highlifter in painted steel

This painted highlifter is ideal for workplaces where many lifts are carried out during the day. The highlifter ensures an excellent working posture as it is possible to adjust it to an ergonomically correct working height by raising or lowering the load.



With manual or electrical lift function
Load capacity: 1,000 kg.

Our highlifter with manual lift function has a "Quick" boost function which is ideal for loads under 100 kg. The electrical highlifter pallet truck is recommended for workplaces where many lifts take place during the day.

On both models, the load is lowered by gripping the lowering handle once either slowly or quickly. The lowering valve provides an infinitely variable lowering speed.

This highlifter has been used as internal handling equipment in production and distribution companies for many years.

Options

- Build-in charger
- Outside fork spread: 480 mm & 685 mm
- Fork length: 700* to 2000 mm
- Stainless steel or galvanized steel
- Powered for compressed air
- * The lift height is reduced at fork length of below 1,200 mm
- Powered for 220 V from mains
- Parking brake
- Automatic lift stops with photocell
- Color of your choice
- Different wheel

Ole Almeborg A/S
Svalhøjvej 15
3790 Hasle, Denmark

+45 56 93 26 00
almeborg.com
facebook.com/OleAlmeborgAS

Product Details

Load capacity:	1,000 kg
Outside spread:	560 mm
Fork length:	1200 mm
Fork height lowered:	90 mm
Lift height pr. pump strokes:	
Up to 100 kg:	28 mm
Over 100 kg:	14 mm
Lowering speed :	Variabel
Steering wheels:	Poly
Load wheels:	Nylon
Weight:	122 kg

Ole Almeborg A/S
Svalhøjvej 15
3790 Hasle, Denmark

+45 56 93 26 00
almeborg.com
facebook.com/OleAlmeborgAS