EURO TUB LIFTER IN STAINLESS STEEL (200L)



OA-2100

Euro Tub Lifter in stainless steel (200L)

Stainless Euro Tub Lifter, specially designed for efficient handling of standard fish and meat bins (200L). This lifter is also suitable for pharmaceutical industries with stringent hygiene requirements. Its ergonomic handle ensures easy maneuverability in



production environments, while effortlessly lifting the tubs from the floor.

The Euro Tub Lifter features an adjustable gripper system specifically designed for lifting plastic tubs. The gripper system securely attaches to the top sharp edge of the tub.

Simplify your operations, ensure worker safety, and maintain high hygiene standards with our Stainless Euro Tub Lifter.

PRODUCT DETAILS

- Load capacity: 250 kg
- Designed for a standard 200L Euro Tub
- Width outside/inside: 810 mm / 660 mm
- Total length: 890 mm
- Lift height 500 mm
- Total height: 1160 mm
- Equipped with nylon wheels for smooth movement
- Bolts, axles, screws, nuts, and split pins made of stainless steel
- An adjustable gripper system is designed to lift the Euro Tub
- The polished pistons and cylinders ensure long-lasting durability of the pump system
- Made in Denmark

HYGIENE

Ole Almeborg A/S Svalhøjvej 15 3790 Hasle, Denmark

- Stainless steel the risk of bacterial attack is minimised
- Developed for environments with severe hygienic requirements
- Easy to clean
- Few hiding places for bacteria

SAFETY

- Features a reliable closed hydraulic system with an automatic free position valve for the handle
- The automatic free position valve prevents the forks from lifting when the handle moves slowly, while allowing normal lifting when the handle is moved faster.

ERGONOMICS

- The lift function makes it easy to lift the tub from the ground
- Designed with user safety and ergonomic working conditions in focus

Options

• For more aggressive environments, we offer the option of an AiSi 316 Stainless chassis and fork carrier truck, which provides enhanced rust resistance.

Product Details

Load capacity:	250 kg
Sizes:	
Width outside / inside:	810 mm / 660 mm
Total length:	890 mm
Total height:	1,160 mm
Lift height:	500 mm
Steering and load wheels:	Nylon
Weight:	76 kg